

# PORTABLE PROPANE CONVECTION HEATERS





Telescoping design for easy assembly. Unpack, lift to lock and you're ready to heat.

### **Temporary Heat For:**

- Construction Sites
- Industrial / Commercial Workspaces
- Agricultural Buildings
- Emergencies
- Workshops
- Remodeling Jobs

America's Most Popular Brand Of Portable Heaters!

## WE HEATER CONTRACTOR SERIES

# BIG HEAT RIGHT OUT OF THE BOX.

- Safe Heater shuts off with loss of flame, sturdy base prevents tip-overs
- Easy Start Push-button pilot light ignition
- Instant Heat Adjustable, economical, and clean burning
- Uniform Heating 360° directional heat
- Economical No electricity required
- Ready To Use Simple hook-up; hose and regulator included
- CSA Certified
- Limited 1-Year Warranty

#### Temporary Heat For Medium Jobs

#### MH80CV 30,000 - 80,000 BTU/HR F270480

Heats approximately 1,900 square feet. Operates up to 14 hours from a 20 lb. (min. required) propane tank.



#### Temporary Heat For Larger Jobs

#### **MH200CV**

propane tank.


75,000 - 200,000 BTU/HR F270600 Heats approximately 4,700 square feet. Operates up to 29 hours from a 100 lb. (min. required)



#### Special Features



Piezo Push Button Ignitor



Adjustable Heat Output Control



"Insta-Lock" System For Easy Assembly – No Tools.



	МН8ОСУ	MH200CV
Stock Number	F270480	F270600
Output (BTU/HR)	30,000 - 80,000	75,000 - 200,000
Fuel	Propane Gas	Propane Gas
Propane Consumption (lbs/hr)	1.4 to 3.7	3.5 to 9.3
Pressure Regulator Settings	11″ W.C.	10 PSI
Flame Safety*	Thermocouple Operated Gas Valve	Thermocouple Operated Gas Valve
Standing Pilot	Yes	Yes
Ignition	Piezo	Piezo
Power Required	None	None
Hose-10ft.	3/8" I.D. w/ Regulator and POL	1/4" I.D. w/ Regulator and POL
POL/Excess Flow Check Valve	Yes	Yes
Shipping Size (L x W x H)	15.25" x 18.25" x 21.75"	18.25" x 15" x 27.5"
Net Weight (Includes Hose/ Regulator / POL Assembly)	19 lbs.	25 lbs.
Shipping Weight	21 lbs.	27 lbs.
Shipping Cube	3.50	4.36

www.mrheater.com

Mr. Heater Inc. 4560 West 160th St. Cleveland, Ohio 44135 • 800-251-0001